

AF-OLK5 Series Fiber Optic Test kit

Product: OLK5 Series

Date: Aug:2007

Rev: 01

Description

The AF-OLK5 series test kits are the complete solution necessary for the installer to test, terminate and trouble shoot fiber optic systems. These test kits are designed to allow testing of all parameters of fiber optic networks, including output power levels from the fiber, coupled source power and attenuation loss in a cable. Plastic Optical Fiber and VSCSEL test kits are also available. The POF kits have modular adapters on both the meter and the 665nm/650nm output of the source.

The AF-OLK51-MM is a test kit designed for multimode applications while the AF-OLK51-SM test kit is designed to test single-mode fiber optic cable. The AF-OLK52-D is designed for both multimode and single-mode applications. The AF-OLK5 series test kits come with the AF-OM100 series power meter. The meter is accompanied with the AF-OS420 for multimode applications and AF-OS430 for single-mode applications. A custom test kit can be made for any application. All kits include a carrying case, one connector adapter, cleaning wipes, power adjustment tool and instructional manual.



Kit Highlights and Key Features

◦ Compact light weight carrying case	◦ On screen testing procedure guides
◦ 650nm, 790nm, 850nm, 1300nm, 1310nm & 1550nm	◦ Meter calibration certificate included
◦ dBm (absolute) + dB (relative) measurement	◦ Display back light
◦ Graphical display with testing guide	◦ Auto power off
◦ Zero reference with dBm value displayed	◦ N.I.S.T. traceable
◦ Optional: 2mm and 3mm Ger detector available for larger core applications	
◦ Single mode and multimode applications	

AF-OM100 Series Power Meter Description

All of the Advanced Fiber Solutions power meters are the perfect tools for measuring optical power, loss (attenuation) and optical return loss in any system, it is just a matter of picking the right instrument for the application. All meters are calibrated at industry standard wavelengths (NIST traceable) for both single-mode and multimode transmitters. All detectors are potted in a threaded housing for versatility and allows the user to interchange adapters for numerous connector types. The AF-OM100 series meters are a low cost series of power meters for the technician who wants a high performance meter. All power meters now come with protective rubber boot.



Highlighted Feature: All our power meters features an on screen testing procedure guide field for quick reference making testing a breeze!

AF-OM100 Series Power Meter

On Screen Testing Procedure Guides	
<p>One Way Loss Test</p>	<p>Two way loss testing guide</p>

AF-OS400 Series Light Source Description

The AF-OS400 series sources offer a complete line of sources for any testing application. Whether testing outside plant or premise an AF-OS400 series optical source will be perfect when combined with an AF-OM100 series optical power meter. On each source all wavelengths are individually adjustable, with the exception of the AF-OS405, allowing the user to use less battery power when high optical output power is not necessary, or to turn up the power to test long runs. This also makes it possible for the AF-OS420 LED source to test single-mode cables up to 5km at 1300nm.



OS400 Series Power Meter

Technical Specifications OM100 Series Power Meters



Optical Specification	AF-OM110	AF-OM120	AF-OM130
Calibrated Wavelengths	650nm, 790nm & 850nm	850nm, 1300nm, 1310nm & 1550nm	1310nm & 1550nm
Measurement Range	+3dBm to -55dBm	+3dBm to -55dBm	+20dBm to -40dBm
Detector Type	Silicon (Si)	Germanium (Ge)	Ger High Power
Applications	Multimode, Premise and Plastic	Single-mode, Multimode, Outside plant and Premise	Single-mode, Long wavelengths, CATV
All Units			
Accuracy (@25°C, -20.0dBm)	±0.25 dB		
Measurement Units	dBm (absolute) - dB (relative)		
Resolution	0.1 dB		
Controls	5 Soft Buttons		
Buttons	On/Off, Backlight, λ, dB-dBm, Zero Reference		
Power	2AA Batteries or AC Power Converter		
Low Battery Indicator	Yes		
Display	Graphical LCD with Backlight		
Adaptor Options	ST, SC, FC, 2.5mm Universal & LC (other adapters also available)		
Auto-Shutdown	Yes		
Protective Rubber Boot	Yes		
Testing Reference Guide	Yes		
Enclosure Size	Compact Handheld (L-4.94"/W-2.75"/H-1.2")		

Temperature Specifications	
Operation Temperature	-10°C to +50°C (45% Hum, non condensing)
Storage Temperature	-20°C to +60°C (75% Hum, non condensing)

Technical Specifications OS400 Series Light Sources



Optical Specification	AF-OS417-MD	AF-OS420	AF-OS430
Wavelengths (λ)	650nm & 850nm	850nm & 1300nm	1310nm & 1550nm
Wavelength Range	850nm \pm 30nm	850nm \pm 30nm 1300nm \pm 30nm	1310nm \pm 5nm 1550nm \pm 5nm
Output Type	LED	LED	Laser
Applications	Plastic, Large core multimode fibers	Premises, campus cabling networks with multimode	Single mode, outside plant and long haul applications
Output Power	>-20.0dBm @ 850 into 62.5 micron fiber	>-20.0dBm @850 & 1300 Into 62.5 micron fiber	>-8.0dBm @1310 & 1550 Into single mode fiber
Stability per hour (after 5 min warm up)	Less than 0.5 dB	Less than 0.05 dB	Less than 0.05 dB
Connector Style	Modular 650nm ST 850nm	ST 1300nm ST 850nm	ST/FC or SC
Modulated Frequencies	N/A	N/A	2Khz
All Units			
Protective Rubber Boot	Yes		
Enclosure Size	Compact Handheld (L-4.94"/W-2.75"/H-1.2")		

Temperature Specifications	
Operation Temperature	-10°C to +50°C (45% Hum, non condensing)
Storage Temperature	-20°C to +60°C (75% Hum, non condensing)

Kit Part Number	Meter	Source	Application
AF-OLK51-MM	AF-OM120	AF-OS420	Multimode
AF-OLK51-SM-ST	AF-OM120	AF-OS430-ST	Single Mode
AF-OLK51-SM-FC	AF-OM120	AF-OS430-FC	Single Mode
AF-OLK51-SM-SC	AF-OM120	AF-OS430-SC	Single Mode
AF-OLK52-D-ST	AF-OM120	AF-OS430-ST, AF-OS420	Single Mode, Multimode
AF-OLK52-D-FC	AF-OM120	AF-OS430-FC, AF-OS420	Single Mode, Multimode
AF-OLK52-D-SC	AF-OM120	AF-OS430-SC, AF-OS420	Single Mode, Multimode
AF-OLK51-P	AF-OM110	AF-OS417-MD	POF and Multimode
AF-OLK53-SM-ST	AF-OM130	AF-OS430-ST	CATV Single Mode
AF-OLK53-SM-FC	AF-OM130	AF-OS430-FC	CATV Single Mode
AF-OLK53-SM-SC	AF-OM130	AF-OS430-SC	CATV Single Mode
AF-OLK53-D-ST	AF-OM130	AF-OS430-ST, AF-OS420	CATV Single Mode, Multimode
AF-OLK53-D-FC	AF-OM130	AF-OS430-FC, AF-OS420	CATV Single Mode, Multimode
AF-OLK53-D-ST	AF-OM130	AF-OS430-SC, AF-OS420	CATV Single Mode, Multimode
Kit Content			
Meter, Source, AD-100 (2.5mm adapter), Batteries, Alco wipes, Trim tool, Manual, Meter calibration cert.			

Note: Advanced Fiber Solutions, Inc offers a full line of connector adapters along with accessory options such as our new 200 power optical inspection microscope. Please contact a distributor for more information.